


**DC Downtown Core Commercial Zone – Section 6 of by law**

This architectural rendering shows a modern building facade. The ground floor is constructed from light-colored bricks and features large glass windows and a glass entrance door. The upper floors are clad in vertical wooden slats, with rectangular windows integrated into the design. To the left, a portion of an adjacent building with a more traditional facade is visible. The scene is set against a clear blue sky and a flat, light-colored ground surface.

REAR



## PROJECT LOCATION



ARCHITECT'S STAMP RELATES ONLY TO THE  
ARCHITECTURAL ITEMS SHOWN ON THIS DRAWING.

DO NOT SCALE OFF DRAWINGS. CONTRACTOR TO SITE VERIFY ALL DIMENSIONS AND REPORT ANY DISCREPANCIES TO ARCHITECT. DRAWINGS ARE THE PROPERTY OF THE ARCHITECT AND ARE NOT TO BE REPRODUCED AND DISTRIBUTED WITHOUT WRITTEN PERMISSION FROM ARCHITECT. DRAWINGS ARE NOT TO BE USED FOR ANY PURPOSE OTHER THAN THE LATEST ISSUE SHOWN BELOW. CONTACT THE ARCHITECT IF VERIFICATION IS REQUIRED TO ENSURE AUTHENTICATION OF ARCHITECT'S SEAL AND OWNERSHIP OF THIS DRAWING AND IT'S CONTENTS

[illegible]


288 KING STREET,  
MIDLAND, ONTARIO  
3RD FLOOR ADDITION

## SITE PLAN

Project number	202505
Date	JULY 7, 2025
Drawn by	JHA INC
Checked by	JHA INC

# A110

Scale 1 : 100






DO NOT SCALE OFF DRAWINGS. CONTRACTOR TO SITE VERIFY ALL DIMENSIONS AND REPORT ANY DISCREPANCIES TO ARCHITECT. DRAWINGS ARE THE PROPERTY OF THE ARCHITECT AND ARE NOT TO BE REPRODUCED AND DISTRIBUTED WITHOUT WRITTEN PERMISSION FROM ARCHITECT. DRAWINGS ARE NOT TO BE USED FOR ANY PURPOSE OTHER THAN THE LATEST ISSUE SHOWN BELOW. CONTACT THE ARCHITECT IF VERIFICATION IS REQUIRED TO ENSURE AUTHENTICATION OF ARCHITECT'S SEAL AND OWNERSHIP OF THIS DRAWING AND ITS CONTENTS

[illegible]

## ELEVATIONS EXTERIOR

# A600

Scale 1 : 50



East

1 : 50

U/S DECK  
9766

U/S 2ND FLOOR DECK  
6540

2ND LEVEL SUB-FLOOR  
3348

GRND SUB-FLOOR  
200

AVERAGE GRADE  
0

10' - 7" NEW

10' - 5 3/4"

10' - 3 7/8"

EXISTING WINDOWS AND DOOR. UNCONFIRMED IF UNPROTECTED OR RATED

C1

C2

W0

W0

1

**CLADDING FINISH**

- MATERIAL: 7/8" CORRUGATED METAL PANEL FROM AGWAY METALS INC.
- C1 - FIELD COLOUR: QC28326 COFFEE
- C2 - ACCENT COLOUR; QC28262 BLACK



**WINDOW COMPARISON OF EXISTING REMOVED AGAINST NEW (WEST ELEVATION)**

- EXISTING TO BE REMOVED - 0.9 M X 0.9 M = 0.81 SM
- NEW W1 - 1.219 M X 1.219 M x 2 = 2.98 SM


DO NOT SCALE OFF DRAWINGS. CONTRACTOR TO SITE VERIFY ALL DIMENSIONS AND REPORT ANY DISCREPANCIES TO ARCHITECT. DRAWINGS ARE THE PROPERTY OF THE ARCHITECT AND ARE NOT TO BE REPRODUCED AND DISTRIBUTED WITHOUT WRITTEN PERMISSION FROM ARCHITECT. DRAWINGS ARE NOT TO BE USED FOR ANY PURPOSE OTHER THAN THE LATEST ISSUE SHOWN BELOW. CONTACT THE ARCHITECT IF VERIFICATION IS REQUIRED TO ENSURE AUTHENTICATION OF ARCHITECT'S SEAL AND OWNERSHIP OF THIS DRAWING AND ITS CONTENTS

[illegible]

# ELEVATIONS EXTERIOR

# A605

Scale 1 : 50



1 North Existing  
1 : 50









PART 3  
PLAN 51R-14973

PLAN 51R-14973

(LOCALLY KNOWN AS) BORSA LANE  
(14' WIDE LANE) (BY REGISTERED PLAN 306)  
P.I.N. 58464-0176(LT)



LEGEND



GENERAL NOTES

- 1) ALL MEASUREMENTS ARE IN METERS, PIPE SIZES ARE IN MILLIMETERS, UNLESS OTHERWISE NOTED.
- 2) LOCATION OF EXISTING SERVICES ARE NOT GUARANTEED. CONFIRM EXISTING UTILITY LOCATIONS AND ELEVATIONS PRIOR TO CONSTRUCTION. THE CONTRACTOR IS REQUIRED TO NOTIFY THE VARIOUS UTILITY COMPANIES 48 HOURS PRIOR TO THE COMMENCEMENT OF ANY WORKS.
- 3) REFER TO THE ACCOMPANYING NOTES DRAWING, DRAWING No. NT-1, FOR THE FULL LIST OF GENERAL, WATERMAIN SERVICING, AND RESTORATION NOTES.

GENERAL NOTES:

1. ALL DIMENSIONS ARE IN METERS UNLESS OTHERWISE NOTED.
2. THE DETAILED TOPOGRAPHIC SURVEY INFORMATION FOR 288 KING STREET HAS BEEN PROVIDED BY DELPHI & JENKINS NORTH LTD., DATED OCT. 9, 2024.
3. THE LEGAL SURVEY INFORMATION HAS BEEN TAKEN FROM THE SURVEYOR'S REAL PROPERTY REPORT OF PART OF LOT 5 (WEST SIDE OF KING STREET), REGISTERED PLAN 306, TOWN OF MIDLAND, COUNTY OF SIMCOE, PREPARED BY DELPHI & JENKINS NORTH LTD., DATED OCT. 9, 2025.
4. THE EXISTING SERVICING INFORMATION HAS BEEN TAKEN FROM THE TOWN OF MIDLAND KING STREET REJUVENATION AS-BUILT DRAWING SET PREPARED BY TATHAM ENGINEERING, DATED APRIL 2022, AND THE 288 KING STREET SERVICE RECORD SHEET, DATED MARCH 2021, AND IS ONLY APPROXIMATE.

SURVEY BENCHMARK INFORMATION:

1. VERTICAL DATUM: DETERMINED BY REALTIME CAN-NET NETWORK OBSERVATIONS (CANADIAN GEODETIC DATUM (CGVD), 1928, 1978 ADJUSTMENT).
2. OBSERVE REFERENCE POINTS UTM (NAD83, CSRS 2010).
- 2.1. PLAN COORDINATE 1 - N 4955711.031, E 588197.433
- 2.2. PLAN COORDINATE 2 - N 4955710.862, E 588255.427
3. BEARING ARE UTM GRID AND ARE DERIVED FROM OBSERVED REFERENCE POINTS 1 AND 2 BY REAL TIME CAN-NET NETWORK OBSERVATIONS AND REFERRED TO THE 6' UTM COORDINATE SYSTEM, ZONE 17, CENTRAL MERIDIAN 81° WEST LONGITUDE (NAD 83, CSRS 2010).

0	FIRST SUBMISSION	NOV 2025 JP
No.	REVISIONS	DATE INITIAL



MIXED-USE SITE PLAN DEVELOPMENT  
288 KING STREET  
TOWN OF MIDLAND, SIMCOE COUNTY  
PRE-DEVELOPMENT STORM  
DRAINAGE AREA PLAN

PARKER CONSULTING  
ENGINEERS LTD.

ADDRESS: 43 HIAWATHA DRIVE, PORT SYDNEY, ONTARIO, P0B 1L0  
TELEPHONE: (705) 796-7208 EMAIL: ParkerConsultingEngineers@Outlook.com


DESIGN: JP	SCALE: 1:100	DATE: NOVEMBER 2025
DRAWN: PCEL-CAD	PROJECT No: 2509001	DRAWING No: STM-1
CHECKED: JP		

C:\Users\parker\OneDrive\PC\Projects\2509001-BASE-KING.dwg Layout:STM-2 Plotted Nov 27, 2025 @ 12:57pm by Parker


PART 3  
PLAN 51R-14973

PLAN 51R-14973

(LOCALLY KNOWN AS) BORSA LANE  
(14' WIDE LANE) (BY REGISTERED PLAN 306)  
P.I.N. 58464-0176(LT)



LEGEND



GENERAL NOTES

- 1) ALL MEASUREMENTS ARE IN METERS, PIPE SIZES ARE IN MILLIMETERS, UNLESS OTHERWISE NOTED.
- 2) LOCATION OF EXISTING SERVICES ARE NOT GUARANTEED. CONFIRM EXISTING UTILITY LOCATIONS AND ELEVATIONS PRIOR TO CONSTRUCTION. THE CONTRACTOR IS REQUIRED TO NOTIFY THE VARIOUS UTILITY COMPANIES 48 HOURS PRIOR TO THE COMMENCEMENT OF ANY WORKS.
- 3) REFER TO THE ACCOMPANYING NOTES DRAWING, DRAWING No. NT-1, FOR THE FULL LIST OF GENERAL, WATERMAIN SERVICING, AND RESTORATION NOTES.

GENERAL NOTES:

1. ALL DIMENSIONS ARE IN METERS UNLESS OTHERWISE NOTED.
2. THE DETAILED TOPOGRAPHIC SURVEY INFORMATION FOR 288 KING STREET HAS BEEN PROVIDED BY DELPH & JENKINS NORTH LTD., DATED OCT. 9, 2024.
3. THE LEGAL SURVEY INFORMATION HAS BEEN TAKEN FROM THE SURVEYOR'S REAL PROPERTY REPORT OF PART OF LOT 5 (WEST SIDE OF KING STREET), REGISTERED PLAN 306, TOWN OF MIDLAND, COUNTY OF SIMCOE, PREPARED BY DELPH & JENKINS NORTH LTD., DATED OCT. 9, 2025.
4. THE EXISTING SERVICING INFORMATION HAS BEEN TAKEN FROM THE TOWN OF MIDLAND KING STREET REJUVENATION AS-BUILT DRAWING SET PREPARED BY TATHAM ENGINEERING, DATED APRIL 2022, AND THE 288 KING STREET SERVICE RECORD SHEET, DATED MARCH 2021, AND IS ONLY APPROXIMATE.

SURVEY BENCHMARK INFORMATION:

1. VERTICAL DATUM: DETERMINED BY REALTIME CAN-NET NETWORK OBSERVATIONS (CANADIAN GEODETIC DATUM (CGVD), 1928, 1978 ADJUSTMENT).
2. OBSERVE REFERENCE POINTS UTM (NAD83, CSRS 2010).
- 2.1. PLAN COORDINATE 1 - N 4955711.031, E 588197.433
- 2.2. PLAN COORDINATE 2 - N 4955710.862, E 588255.427
3. BEARING ARE UTM GRID AND ARE DERIVED FROM OBSERVED REFERENCE POINTS 1 AND 2 BY REAL TIME CAN-NET NETWORK OBSERVATIONS AND REFERRED TO THE 6' UTM COORDINATE SYSTEM, ZONE 17, CENTRAL MERIDIAN 81° WEST LONGITUDE (NAD 83, CSRS 2010).

No.	REVISIONS	DATE	INITIAL
0	FIRST SUBMISSION	NOV 2025	JP



MIXED-USE SITE PLAN DEVELOPMENT  
288 KING STREET  
TOWN OF MIDLAND, SIMCOE COUNTY  
POST-DEVELOPMENT STORM  
DRAINAGE AREA PLAN

PARKER CONSULTING ENGINEERS LTD.		
ADDRESS: 43 HIAWATHA DRIVE, PORT SYDNEY, ONTARIO, P0B 1L0 TELEPHONE: (705) 796-7208 EMAIL: ParkerConsultingEngineers@Outlook.com		
DESIGN: JP	SCALE: 1:100	DATE: NOVEMBER 2025
DRAWN: PCEL-CAD	PROJECT No: 2509001	DRAWING No: STM-2
CHECKED: JP		

C:\Users\parker\OneDrive\PC\Projects\2509001-288 King St\04-CAD\2509001-BASE-KING.dwg Layout:04-1 Plotted Nov 27, 2025 @ 12:57pm by Parker

TOWN OF MIDLAND GENERAL NOTES

- 1) ALL MEASUREMENTS ARE IN METERS, PIPE SIZES ARE IN MILLIMETERS, UNLESS OTHERWISE NOTED.
- 2) LOCATION OF EXISTING SERVICES ARE NOT GUARANTEED. CONFIRM EXISTING UTILITY LOCATIONS AND ELEVATIONS PRIOR TO CONSTRUCTION. THE CONTRACTOR IS REQUIRED TO NOTIFY THE VARIOUS UTILITY COMPANIES 48 HOURS PRIOR TO THE COMMENCEMENT OF ANY WORKS.
- 3) ONTARIO PROVINCIAL STANDARDS SPECIFICATIONS (OPSS), ONTARIO PROVINCIAL STANDARD (OPSD), AND THE TOWN OF MIDLAND'S STANDARDS SHALL APPLY TO ALL WORKS TAKING PLACE IN THE TOWN BOUNDARIES.
- 4) ORDER OF PRECEDENCE OF STANDARD DRAWINGS IS FIRSTLY TOWN OF MIDLAND ENGINEERING DEVELOPMENT DESIGN STANDARDS, SECONDLY THE ONTARIO PROVINCIAL STANDARD DRAWINGS (OPSD).
- 5) ROAD OCCUPANCY PERMIT IS REQUIRED FROM THE TOWN OF MIDLAND PRIOR TO THE COMMENCEMENT OF WORK WITHIN ANY TOWN RIGHT-OF-WAY.
- 6) CONTRACTOR SHALL COORDINATE HIS WORK SUCH THAT HE DOES NOT INTERFERE WITH WORK BEING UNDERTAKEN BY A UTILITY COMPANY.
- 7) UTILITIES CROSSING, WHERE REQUIRED, SHALL BE SUPPORTED AS PER OPSD 1007.01 AND ANY EXISTING STRUCTURES SHALL BE PROPERLY SUPPORTED.
- 8) DRIVEWAY ACCESS TO OCCUPIED RESIDENCES SHALL BE RESTORED AT THE END OF EACH WORKING DAY.
- 9) NATIVE MATERIAL SUITABLE FOR BACKFILL SHALL BE COMPACTED TO 98% STANDARD PROCTOR MAXIMUM DRY DENSITY, UNLESS OTHERWISE NOTED. ENGINEERED FILL (ON LOTS) SHALL BE COMPACTED TO 100% STANDARD PROCTOR MAXIMUM DRY DENSITY.
- 10) GRANULAR MATERIAL AND BEDDING MATERIAL SHALL BE PLACED IN LAYERS 150mm IN DEPTH AND COMPACTED TO 98% (ROAD GRAN "A" & GRAN "B") OR 98% (BEDDING AND COVER) STANDARD PROCTOR MAXIMUM DRY DENSITY OR AS DIRECTED BY THE SOILS CONSULTANT.
- 11) ALL DISTURBED AREAS WITHIN EXISTING MUNICIPAL RIGHT-OF-WAYS ARE TO BE REINSTATE TO THEIR ORIGINAL CONDITIONS OR BETTER AS DETERMINED BY THE TOWN OF MIDLAND (MIN.150MM TOPSOIL AND SOD). ALL OTHER DISTURBED AREAS TO BE TOPSOILED AND SEEDED PRIOR TO ACCEPTANCE.
- 12) ALL SILT CONTROL AND EROSION PROTECTION DEVICES ARE TO BE IN PLACE PRIOR TO THE COMMENCEMENT OF CONSTRUCTION AND SHALL REMAIN IN PLACE AND BE MAINTAINED BY THE CONTRACTOR UNTIL CONSTRUCTION IS COMPLETE. THE GRASS HAS ESTABLISHED GROWTH AND APPROVED BY TOWN ENGINEER.
- 13) ALL GRADING MUST BE CONFIRMED BY THE TOWN OF MIDLAND ENGINEERING DEPARTMENT.
- 14) ALL SIDEWALKS SHALL BE CONSTRUCTED ON A PROPERLY CONSTRUCTED FOUNDATION OF 150mm MINIMUM DEPTH OF GRANULAR "A" AND BE PAVED WITH CONCRETE FULL WIDTH, THICKNESS TO BE 200mm ACROSS COMMERCIAL AND INDUSTRIAL ENTRANCES. ALL CONCRETE MATERIALS AND WORK SHALL CONFORM TO OPSS USING THE TOWN OF MIDLAND CONCRETE MIX DESIGN.
- 15) CHAIN LINK FENCE INSTALLED AS PER OPSD 972.130 WITH TOP RAIL, KNUCKLED TOP EDGE FASTNERS, KNUCKLED BOTTOM EDGE AND NO. 9 GAUGE WIRE.
- 16) ALL SEWER SYSTEMS INCLUDING SERVICE CONNECTIONS TO THE PROPERTY LINE, MANHOLES AND CATCHBASINS SHALL BE THOROUGHLY FLUSHED AND/OR CLEANED OF DEBRIS AND ALL PIPES SHALL BE TESTED IN ACCORDANCE WITH OPS AND SHALL BE INSPECTED BY AN APPROVED VIDEO CAMERA TESTING COMPANY AND THE TOWN ENGINEER SHALL BE PROVIDED A COPY OF APPROPRIATE DATA UPON COMPLETION OF CONSTRUCTION AND PRIOR TO FINAL APPROVAL. ANY SECTION OF SEWER OR SERVICE CONNECTION THAT FAIL TO MEET THE REQUIREMENTS SHALL BE REPAIRED OR REPLACED AT THE DIRECTION OF THE TOWN ENGINEER. ONLY CHEMICAL PRESSURE GROUTING REPAIR TECHNIQUES WILL BE CONSIDER ACCEPTABLE.

TOWN OF MIDLAND WATERMAIN NOTES

- 1) A) WATERMAIN MATERIAL TO BE PVC(CLASS 235, DR-18) AND, SHALL SATISFY AWWA C900-16 SPECIFICATION.
- B) MECHANICAL JOINT FITTINGS MEETING AWWA SPECIFICATIONS C-907 AND CSA B137. WATERMAIN SHALL BE USED WHERE APPLICABLE ON 150mm TO 400mm PVC WATERMAIN. SHOULD DUCTILE IRON MECHANICAL JOINT FITTINGS BE EMPLOYED THE CONTRACTOR SHALL INSTALL SACRIFICIAL CAPS ON EVERY NUTS ON EVERY BOLT. PVC JOINTS USING MECHANICAL JOINT FITTINGS ARE TO BE SQUARE CUT, NOT BEVELED.
- C) MINIMUM RESIDENTIAL SERVICE TO BE 25mm MUNICIPEX WITH TRACERWIRE.
- 2) A) WATERMAIN SHALL BE CONSTRUCTED WITH BEDDING AS PER OPSD 802.010 GRANULAR "A" FOR FLEXIBLE PIPES AS OPSD 802.030 OR 802.031 CLASS "B". GRANULAR "A" BEDDING MATERIAL OR SELECT NATIVE COVER MATERIAL FOR RIGID PIPE UNLESS OTHER APPROVED BY THE TOWN OF MIDLAND.
- B) SERVICES 25mm TO 50mm IN DIAMETER SHALL BE EMBEDDED IN SAND OR "A" GRAVEL 100mm ABOVE AND BELOW TO CONFORM TO OPSS 1004.05.
- 3) CONTRACTOR SHALL INFORM THE TOWN OF MIDLAND A MINIMUM OF 48 HOURS IN ADVANCE IF THEIR INTENTIONS TO COMMENCE WORK.
- 4) CONTRACTOR TO BE RESPONSIBLE FOR INSTALLATION AND MATERIALS TO INSTALL ON INITIAL TIE-IN REQUIRED TO FACILITATE THE TESTING OF THE NEWLY INSTALLED DISTRIBUTION SYSTEM PRIOR TO CONNECTIONS TO THE EXISTING SYSTEM. WATERMAIN TO BE PRESSURE TESTED, SWABBED AND CHLORINATED BY THE CONTRACTOR, UPON SUCCESSFUL TEST RESULTS, THE FINAL TIE-IN TO BE COMPLETED BY CONTRACTOR WITH THE TOWN OF MIDLAND SUPERVISION AND ASSISTANCE WITH OPERATING THE EXISTING WATER SYSTEM FOR A WATER SYSTEM SHUT-OFF. RISER PIPES ARE TO BE INSTALLED AS PER STANDARD, AND REMOVED AS DIRECTED. SWABBING/TESTING SCHEDULE TO BE SUPPLIED BY THE CONTRACTOR TO THE TOWN OF MIDLAND TO REVIEW AND APPROVE.
- 5) THE CONTRACTOR IS RESPONSIBLE FOR THE SWABBING, PRESSURE TESTING, CHLORINATION AND FLUSHING BEYOND THE INITIAL PROCEDURE WILL BE AT THE CONTRACTORS EXPENSES AND AT THE DISCRETION OF THE TOWN OF MIDLAND. THE CONTRACTOR SHALL MAKE ALL CONNECTIONS TO THE EXISTING WATERMAINS INCLUDING EXCAVATION, BACKFILLING, AND MATERIALS AS REQUIRED, UNDER THE TOWN OF MIDLAND'S SUPERVISION.
- 6) CONTRACTOR TO USE THE TOWN OF MIDLAND WATERMAIN COMMISSIONING PROCEDURE. GENERAL INSTALLATION AND TESTING WATERMAIN AND APPURTENANCES TO BE IN ACCORDANCE WITH OPSS 421.01MUM, OPSS 411 AND TOWN WATERMAIN COMMISSIONING PROCEDURE.
- A) ALL WATERMAINS ARE TO BE SWABBED USING A MINIMUM OF 2 CLEAN NEW MARKED SWABS 2" LARGER THAN THE PIPE DIAMETER AND FLUSHED BY THE CONTRACTOR'S ENGINEER AND THE TOWN'S REPRESENTATIVE TO BE PRESENT DURING THE TESTING.
- B) WATERMAINS SHALL NOT BE CONNECTED TO THE EXISTING WATERMAIN UNTIL BACTERIOLOGICAL TESTING HAS BEEN SUCCESSFULLY COMPLETED.
- C) THE TOWN AND ENGINEER TO RECEIVE A MINIMUM 72 HOURS NOTICE PRIOR TO TESTING OF THE WATERMAINS.
- 7) ALL NEW SERVICE BOXES TO BE LOCATED ON PROPERTY LINE AND OUT OF THE DRIVEWAY AND SIDEWALKS.
- 8) NO WATERMAIN IS TO BE LAID ON FILL UNTIL THE DENSITY REPORT HAS BEEN SUBMITTED TO AND APPROVED BY THE ENGINEER. FILL TO BE PLACED TO 0.6m MINIMUM ABOVE THE TOP OF THE WATERMAIN GRADED AND COMPACTED AS PER OPSS 501. TESTS SHALL BE TAKEN ALONG THE CENTER LINE OF THE WATERMAIN AND 2.5m EITHER SIDE OF THE WATERMAIN AT A MAXIMUM INTERVAL OF 30m FOR EACH 0.6m LIFT. ALL TEES, HORIZONTAL BENDS, AND BRANCH VALVES IN FILL AREAS TO BE TIED WITH TIE RODS IN ADDITION TO CONCRETE BLOCKING ACCORDING TO NOTE 8.
- 9) A) THRUST BLOCKING: CONCRETE THRUST BLOCKS ARE TO BE INSTALLED AT ALL TEES, BENDS, ENDS OF MAINS AND CONNECTIONS 100mm AND LARGER AS PER OPSD 1103.010 AND 1103.020 AND THE TOWN OF MIDLAND STANDARD DRAWINGS STD-R13. AT ALL THRUST BLOCK LOCATIONS RESTRAINING DEVICES ARE REQUIRED IN ADDITION TO STANDARD CONCRETE THRUST BLOC:KING.
- B) ALL SEGMENTS OF THE FITTING AND THE WATERMAIN AT THE THRUST BLOCK LOCATION SHALL BE RESTRAINED AT LEAST 10m EACH SIDE OF THE THRUST BLOCK WHERE THE DEFLECTION ANGLE AT THE THRUST IS MORE THAN 11-1/4". TIE RODS AND CLAMPS SHALL BE GIVEN TWO COATS OF BITUMASTIC PAINT.
- C) IMPORTED GRANULAR FILL (OPS GRANULAR "A" OR EQUIVALENT) IS TO BE USED BEHIND THE THRUST BLOCK AND FOR A MINIMUM

- DISTANCE OF 2m EACH SIDE OF THE THRUST BLOCK. THIS IMPORTED GRANULAR FILL IS TO BE COMPACTED TO A MINIMUM OF 100% STANDARD PROCTOR MAXIMUM DRY DENSITY. PRIOR TO CONSTRUCTION OF THE THRUST BLOCKS THE CONTRACTOR SHALL OBTAIN THE WRITTEN APPROVAL OF THE BACKFILL FROM A QUALIFIED GEOTECHNICAL ENGINEER.
- 10) ROMAC GRIP RINGS TO BE USED ON ALL MECHANICAL FITTINGS.
- 11) CONTRACTOR TO PERFORM CONSTRUCTION SUCH THAT WATER SERVICE IS MAINTAINED AT ALL TIMES.
- 12) TRACING WIRE TO BE INSTALLED ON TOTAL LENGTH OF PVC WATERMAIN (#12 TWJ STRANDED COPPER FOR OPEN CUT CONSTRUCTION OR #8 TWJ FOR DIRECTIONAL BORING INSTALLATION), BROUGHT TO SURFACE AT ALL WATER VALVE BOXES AND COILED UNDER THE VALVE BOX CAPS.
- 13) INSULATE WATER SERVICES WITH HI-40 INSULATION WHERE 0.5m SEPARATED FROM OTHER UTILITIES CANNOT BE MAINTAINED. INSULATION TO EXTEND 0.5M BEYOND OUTSIDE DIAMETER OF BOTH PIPES.
- 14) WHERE WATER SERVICES CONFLICT WITH OTHER UTILITIES, DEFLECT SERVICE 50 AS TO PROVIDE A MIN. 0.5m CLEARANCE. MAINTAIN MIN. DEPTH OF COVER AT ALL TIMES.
- 15) SERVICE CONNECTIONS SHALL BE PLACED AT A MINIMUM SEPARATION OF 1.0m AND A MINIMUM OF 0.6m FROM JOINTS. (ENDS OF PIPE).
- 16) MINIMUM HORIZONTAL CLEARANCE BETWEEN WATERMAIN AND SEWERS TO BE 2.5 METERS.
- 17) A) FIRE HYDRANT TO BE CANADA VALVE CENTURY/PREMIERE MODEL OPENING COUNTER CLOCKWISE, AWWA C502 WITH STORTZ PUMPER ATTACHMENTS (SEE TOWN OF MIDLAND, TYPICAL HYDRANT AND VALE INSTALLATION DETAIL ON STD-R6)
- B) VALVES: MUELLER RESILIENT SEAT AWWA C509
- C) VALVE BOXES: BIBBY
- D) SADDLES: ROCKWELL 371 & 372
- E) MAIN STOP: MUELLER AWWA C800
- F) CURB STOP: MUELLER AWWA C800
- G) SERVICE BOXES: MUELLER WITH STAINLESS STEEL RODS
- 18) FIRE HYDRANT TO BE OFFSET 0.3m FROM ANY PROPERTY LINE, AND 1.5m FROM ANY DRIVEWAY.
- 19) MINIMUM DEPTH OF COVER OVER WATERMAIN TO BE 1.8m AS SHOWN IN THE TOWN OF MIDLAND STANDARD DETAILS.
- 20) WHERE 25mm SERVICE CANNOT MAINTAIN 1.7m DUE TO ELEVATIONS OF UTILITIES, THE CONTRACTOR SHALL INSTALL 4.0m OF 100MM PVC SDR28 LINER A MINIMUM OF 0.5m BELOW THE UTILITY.
- 21) WHERE WATERMAIN CONFLICTS WITH SEWER PIPES, DEFLECTION WATERMAIN OVER SEWERS DO NOT USE BENDS IF POSSIBLE. PROVIDE A MINIMUM OF 0.5m CLEARANCE BETWEEN WATERMAIN AND SEWERS. MAINTAIN MINIMUM DEPTH OF COVER OF 1.7m AT ALL TIMES.
- 22) MINIMUM HORIZONTAL SEPARATION BETWEEN WATERMAIN AND SEWERS TO BE 2.5m.
- 23) ALL VALVES TO BE RESILIENT CLOW CANADA F6100 SEAT GALE VALVES.
- 24) PRESSURE REDUCING VALVES SHALL BE CLA-VAL MODEL 90-48 (OR EQUIVALENT) COMPLETE WITH DIRT/LYN SLEEVES AND PRESSURE GAUGES IN 1500 VALVE CHAMBER OPSD 1101.010 C/W SUMP.
- 25) DOUBLE CHECK VALVES (FOR FUTURE PRIVATE SITE PLAN WORKS) SHALL BE 150mm WATTS SERIES 909 OR APPROVED EQUIVALENT.
- 26) VALVES IN EXC ESS OF 1.7m IN DEPTH SHALL REQUIRE A VALVE STEM EXTENSION.
- 27) RISER PIPES ARE TO BE INSTALLED AS PER STANDARD, AND REMOVED DIRECTED.
- 28) CATHODIC PROTECTION OF ALL WATERMAIN FITTINGS AND APPURTENANCES TO BE PROVIDED AS PER TOWN STANDARD. THE ANODE SHALL BE CONNECTED USING THE "CADWELD" METHOD INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS. ALL "CADWELDS" ARE TO BE COVERED WITH ROYSTON HANDY CAMP PATCH. THE ANODE SHALL BE CONNECTED TO MAIN STOP AND CURB STOP IN CONJUNCTION WITH AN ELECTRICAL BRASS GROUNDING CLAMP. ALL FITTING BOLTS ARE TO BE FITTED WITH 19mm SACRIFICIAL ZINC CAPS.

TOWN OF MIDLAND ROAD NOTES

1. SUBGRADE AND BOULEVARD MATERIAL TO BE COMPACTED TO BE COMPACTED TO A DRY DENSITY OF AT LEAST 95% OF THE MATERIAL'S SPMD0.
2. GRANULAR A AND B TO BE COMPACTED TO A DRY DENSITY OF AT LEAST 100% OF THE MATERIAL'S RESPECTIVE SPMD0.
3. CURB AND GUTTER TO BE BARRIER CURB AS PER OPSD 600.010 (COMMERCIAL, MULTI-RESIDENTIAL, RESIDENTIAL) IN ALL ROADS. CURBS TO BE SINGE STAGE ONLY, UNLESS APPROVED BY TOWN OF MIDLAND.
4. ROAD WORKS TO CONFORM TO STD-R1 TO STD-R5, R.O.W 20m, 26m, AND 30m.
5. ROADS SHALL BE KEPT CLEAN DURING CONSTRUCTION AT THE CONTRACTOR'S EXPENSE.
6. SIDEWALKS TO COMPLY WITH OPSD 310.010 AND ARE TO BE 1.5M WIDE. MINIMUM THICKNESS AS FOLLOWS:  
A) RESIDENTIAL DRIVEWAY 150mm  
B) COMMERCIAL/INDUSTRIAL DRIVEWAY 200mm (REINFORCEMENT AS PER OPSS IF REQUIRED)
7. NATIVE SUBGRADE SHALL HAVE A CROSSFALL OF 3% AND THE MATERIAL SHALL BE APPROVED BY A GEOTECHNICAL CONSULTANT.
8. ROAD SURFACE TO HAVE AN CROSS FALL OF 2%.
9. ALL CURB RADII TO BE MINIMUM OF 10.0 METERS AT THE EDGE OF ASPHALT.
10. CURBS TO BE DEPRESSED AT INTERSECTION FOR SIDEWALKS PER OPSD 310.030.
11. NATIVE SUBGRADE TO BE COMPACTED TO MINIMUM 98% STANDARD PROCTOR MAXIMUM DRY DENSITY AND SHALL BE TESTED BY THE GEOTECHNICAL CONSULTANT.
12. THE ROAD AND CROSS SECTION SHALL INCORPORATE 150mm B SUBDRAIN WITH FACTORY INSTALLED FILTER FABRIC (OPSD 216.021) AS REQUIRED.
13. GRADE AND CROSS FALL ADJUSTMENT OF MAINTENANCE HOLE AND CATCHBASIN FRAMES SHALL BE MADE USING PRODUCTS SPECIFICALLY MANUFACTURED FOR THAT PURPOSE. CAST IRON ADJUSTMENT UNITS SHALL BE USED FOR ALL MAINTENANCE HOLE AND CATCH BASIN GRATES TO BE SET AT PROPER GRADES FOR SURFACE COURSE ASPHALT ONLY. ALL OTHER ADJUSTMENTS UNITS FOR ALL MAINTENANCE AND CATCHBASIN FRAME AND GRATES SHALL BE CONCRETE (PER OPSD 704.010). ALL MAINTENANCE, CATCH BASINS, ETC SHALL HAVE A MAX OF 300MM OF ADJUSTMENT TO ALLOW FOR FUTURE ADJUSTMENT UP OR DOWN.
14. ADJUSTMENT UNITS SHALL BE CERTIFIED TO MEET ALL PERTINENT OPS, CSA, ASTM, AND MTO-DSM LIST, OR OTHER INDUSTRY GUIDELINES FOR MATERIALS, PERFORMANCE AND USE AS APPLICABLE.
15. ADJUSTMENT UNITS AND JOINTS SHALL BE SEALED AND OR PARGED IN COMPLIANCE WITH MANUFACTURERS SPECIFICATIONS AND GUIDELINES.
16. MORTAR SHALL BE USED FOR LEVELING PRECAST UNITS ONLY, THE THICKNESS OF MORTAR SHALL BE 10mm TO FILL ALL VOIDS CREATED BY IRREGULARITIES IN THE PRECAST UNITS TO ENSURE AN EVEN SURFACE ONLY.
17. NON-COMPRESSIBLE BACKFILL SHALL BE USED DURING REBUILDING, ADJUSTING, OR ANY OTHER APPLICABLE CATCHBASIN OR MAINTENANCE HOLES WORKS.
18. DRIVEWAY APRONS TO BE CONSTRUCTED  
A) RESIDENTIAL – MIN 50mm HL3 ON MIN. 200mm GRAN "A".  
B) COMMERCIAL – MIN 50mm HL3 ON MIN. 250mm GRAN "A" AND MIN 300mm GRAN "B".
19. UNDERGROUND CONDUIT:  
THE CONTRACTOR SHALL SUPPLY AND INSTALL 100MM "HEAVY-WALLED" RIGID PVC CONDUIT, SCEOTRE/CANRON TYPE 2 OR APPROVED EQUIVALENT AS PER CSA STANDARDS C22. NO. 212.2 ALL COUPLINGS, ELBOWS, ETC. SHALL BE BONDED WITH ADHESIVES RECOMMENDED BY THE CONDUIT MANUFACTURER IN A MANNER THAT PREVENTS THE ENTRY OF MOISTURE AND BACKFILL MATERIAL, ETC. THE CONDUIT SHALL BE INSTALLED IN LOCATIONS, AS NOTED ON THE CONTRACT DRAWINGS, AT A MINIMUM DEPTH F 0.6m BELOW FINISHED GRADE. BACKFILL SHALL CONFORM TO THE REQUIREMENTS OF PSS FORM 1010, GRAN "A" AND GRAN "B" TYPE 1 AND SHALL BE COMPACTED TO 100% MAXIMUM DRY DENSITY. EARTH BACKFILL SHALL BE COMPACTED TO 98% MAXIMUM DRY DENSITY.
20. A 400N TEST STRENGTH NYLON ROPE "FISH LINE" SHALL BE PLACED WITHIN EACH RUN OF CONDUIT WITH 1.5M OF EXCESS ROPE LEFT COILED WITHIN THE CHAMBERS AT EACH END OF THE CONDUIT.
21. CONCRETE ELECTRICAL HANDHOLES:  
HANDHOLES SHALL INCLUDE CAST IRON COVERS, SONO TUBES AND CONCRETE. THE INSIDE DIAMETER SHALL BE 0.46M. OAKS PRECAST OR APPROVED EQUIVALENT HANDHOLES THAT CONFORM TO OPSD 211.02 MAY BE USED. CAST IN PLACE HANDHOLES MUST HAVE INSIDE CHAMBERS SONO TUBE REMOVE WHEN CONCRETE HAS HARDENED. THE NUMBER AND ORIENTATION OF CHAMBER ENTRY SLEEVES SHALL BE IN ACCORDANCE WITH THE CONTRACT DRAWINGS. THE TOP OF THE JUNCTION BOX SHALL BE SET TO AN ELEVATION THAT CONFORMS TO THE SURROUNDING ELEMENTS (E.G. CURBS, SIDEWALK, ETC.). ALL HANDHOLES SHALL HAVE LIDS FASTENED AND LIFT RINGS REMOVED.
22. EACH CHAMBER SHALL PROVIDE FOUR (4) SPARE AND CAPPED ENTRY SLEEVES SPACED EVENLY AT NINETY DEGREE INTERVALS AROUND THE CIRCUMFERENCE OF THE CHAMBER IN ADDITION TO THE ENTRY POINTS FOR THE ROAD CROSSING CONDUITS.
23. DURING INSTALLATION OF UNDERGROUND CONDUIT AND CONCRETE ELECTRICAL HANDLES FOR THE TRAFFIC SIGNALS, A REPRESENTATIVE FROM THE TOWN OF MIDLAND PUBLIC WORKS DEPARTMENT IS TO BE PRESENT

GENERAL NOTES:

1. ALL DIMENSIONS ARE IN METERS UNLESS OTHERWISE NOTED.
2. THE DETAILED TOPOGRAPHIC SURVEY INFORMATION FOR 288 KING STREET HAS BEEN PROVIDED BY DELPH & JENKINS NORTH LTD., DATED OCT. 9, 2024.
3. THE LEGAL SURVEY INFORMATION HAS BEEN TAKEN FROM THE SURVEYOR'S REAL PROPERTY REPORT OF PART OF LOT 5 (WEST SIDE OF KING STREET), REGISTERED PLAN 306, TOWN OF MIDLAND, COUNTY OF SIMCOE, PREPARED BY DELPH & JENKINS NORTH LTD., DATED OCT. 9, 2025.
4. THE EXISTING SERVICING INFORMATION HAS BEEN TAKEN FROM THE TOWN OF MIDLAND KING STREET REJUVENATION AS-BUILT DRAWING SET PREPARED BY TATHAM ENGINEERING, DATED APRIL 2022, AND THE 288 KING STREET SERVICE RECORD SHEET, DATED MARCH 2021, AND IS ONLY APPROXIMATE.

SURVEY BENCHMARK INFORMATION:

1. VERTICAL DATUM: DETERMINED BY REALTIME CAN-NET NETWORK OBSERVATIONS (CANADIAN GEODETIC DATUM (CGVD), 1928, 1978 ADJUSTMENT).
2. OBSERVE REFERENCE POINTS UTM (NAD83, CSRS 2010)
- 2.1. PLAN COORDINATE 1 – N 4955711.031, E 588197.433
- 2.2. PLAN COORDINATE 2 – N 4955710.862, E 588255.427
3. BEARING ARE UTM GRID AND ARE DERIVED FROM OBSERVED REFERENCE POINTS 1 AND 2 BY REAL TIME CAN-NET NETWORK OBSERVATIONS AND REFERRED TO THE 6° UTM COORDINATE SYSTEM, ZONE 17, CENTRAL MERIDIAN 81° WEST LONGITUDE (NAD 83, CSRS 2010).

0	FIRST SUBMISSION	NOV 2025	JP
No.	REVISIONS	DATE	INITIAL



MIXED-USE SITE PLAN DEVELOPMENT  
288 KING STREET  
TOWN OF MIDLAND, SIMCOE COUNTY

NOTES

PARKER CONSULTING  
ENGINEERS LTD.

ADDRESS: 43 HIAWATHA DRIVE, PORT SYDNEY, ONTARIO, P0B 1L0  
TELEPHONE: (705) 796-7208 EMAIL: ParkerConsultingEngineers@Outlook.com

DESIGN: JP	SCALE: 1:100	DATE: NOVEMBER 2025
DRAWN: PCEL-CAD	PROJECT No: 2509001	DRAWING No: NT-1
CHECKED: JP		